

**WISTRON Forklift - Reach Truck Wireless Camera System  
 SP-7700H2W**



Forklift wireless camera system for reach trucks and other types of industrial trucks used for lifting.

Lift truck operators work every day in situations where their vision is limited. whether at the fork tips, or behind the truck, increases handling times and may also result in dropped loads, damaged goods, bent racking or picking the wrong pallet.

720P Stainless Steel Wireless Camera built in 2.4GHz Digital Wireless Transmitter. Mobile power output:DC 12V(0.6A),easy to install,no need to Run Cables.

**Specifications :**

<b>Digital Wireless Receiver Monitor (Model: SP-7700H2)</b>
7" HD Screen Monitor with Removable Sun Visor
Built in 2 CH 2.4GHz Digital Wireless Receiver
Operation Frequency:2400 ~ 2483.5MHz
Receiving Sensitivity: -86dBm(1MHZ QPSK MD300RE)
Overlapping Hopping Channel:80
Color System:PAL/NTSC
Display Resolution: 1024RGB(H) X 600(V) dot
Wide view angle(CR>10):(up/ down): 50/70 (left/right): 70/70
Back-light : Single LED 600cd/m2 Brightness
Contrast ratio: 500:1
Operating temperature: -20°C to +70°C
Storage temperature: -30°C to +80°C
Free Operating Voltage: DC8~32V
External dimensions:L*W*T(207X149.5X85)mm(without mounting)
Weight Approx: 600g

**Stainless Steel Wireless Camera (Model: SS-8305H-W)**

Image Type: 1/3.7 inch Color CMOS  
 Built in 2.4GHz Digital wireless transmitter  
 Transmission Power:18dBm with Power control  
 Line of Sight Range: 100M  
 Horizontal Resolution:720P  
 Effective pixel:PAL:1280(H)X960(V)  
 Usable Illumination : 1Lux  
 Free viewing angle: 45°  
 Waterproof: IP69K  
 Shockproof: 10G  
 Free Operating Voltage: DC12 Volts for power bank  
 Dimensions: 25(W) x 37(H) x 124(D) mm (without mounting)  
 Weight : 450g

**Mobile Power Bank (Model: SP-DC12V)**

Type Batteries:Polymer Batteries  
 Capacity:8000mAH  
 DC Input:12.6V/3A  
 DC Output::12(3A)  
 Charging times:> 800 cycles  
 Charge / Discharge Interface:DC2.1 \* 5.5 male  
 Shockproof Level:10G  
 Waterproof Level:IP66  
 Charging Working Temperature: 0 °C to + 40°C  
 Discharge Working Temperature:-20°C to + 60 °C  
 Storage Temperature:-40 °C to + 60 °C  
 Dimensions (mm):136.5mmX120mmx49mm  
 Weight (g):1200g  
 Fitting:Charging cable ,manual,External magnetic (optional)

**Accessorie**

U- Support Bracket,Angle Adjustment Screw,Removable Sun Visor,Electrical Connecting Cable,Antenna\*1,User's Manual

